



P640i

SECURITY



P640i Card Printer

Key Features

- » Full Color Dual-Sided Card Printing and Dual-Sided Lamination
- » Micro Card Positioning for Excellent Color Registration and Superior Print Quality
- » Numerous Security Features (covert printing, Secure ID/Key, ID/Log)
- » Built-in Ethernet for Network Capability (optional)

*i*series

A Complete Security Solution for Tamper Resistant ID Cards

Adding unique security features to ID cards is easier, faster, more economical with Zebra's P640i. This next generation printer from Zebra delivers mission-critical reliability and superior affordability. Protect your ID cards from counterfeiting, alteration or duplication with the P640i's customizable levels of security. Zebra is one of the first manufacturers to offer an extended range of security options for all printing components - cards, ribbons, laminates and printers. When security counts, count on Zebra.

Use the P640i printer for:

- » Agency Licenses
- » High Security Access Control ID Cards
- » Law Enforcement and Correctional Facility ID Cards
- » Airport ID Cards
- » Any card application requiring long lasting, secure issuance of tamper-resistant ID's

Many "Best In Class" features:

- » Lowest consumables cost per card in the industry
- » Highest production output speed with continuous card loading feature.
- » Superior print quality for optimal color fidelity and precision details
- » Reliable and easy to use



**Card
Printer
Solutions**

P640i

Card Printer Product Specifications



General Specifications

- » Dual-sided printing and one-pass waste-free lamination
- » 120 cards/hour dual-sided printing and laminating (YMCK ribbon & 1.0 mil laminate both sides)
- » Micro-positioning card transport system for enhanced color photos
- » Complete system security features & options for printer, ribbons, laminate, cards, and card issuance process
- » Covert printing capability text approx 17 mil high
- » Automated card cleaning before printing
- » Built-in Ethernet option for networking capability
- » Windows® drivers for 2000 and XP with advanced security features (ID/Log & password protection)
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Color Printing

- » Color dye sublimation and resin K
- » 30 seconds per card (YMCK & dual sided lamination)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Bar codes and other symbologies available via Windows driver

Fonts

- » True Type or other type fonts via Windows driver

Card Specifications

- » Types: PVC Composite
- » Card width/length: ISO CR-80 - ISO 7810 2.12" (54mm) x 3.38" (86mm)
- » HiCo Magnetic Stripe - ISO 7811
- » Contact Smart Card - ISO 7816 Compliant
- » Contactless Smart Card - Mifare® or HID iClass™
- » Card thickness: 27 mil - 39 mil
- » Card input hopper capacity: 150 cards

Ribbon Specifications

- » YMCK: 600 cards/roll
- » YMCKK: 500 cards/roll
- » YMCUVK: 500 cards/roll
- » Cleaning cartridge: cleans 3,000+ cards



www.zebracard.com

Laminate Specifications

- » Linerless & wastefree 1.0 mil laminate, 600 cards/roll
- » 2 Laminate cassettes (upper & lower)
- » Laminates available:
 - Clear full size, clear for magnetic stripe cards and clear for smart cards. Custom laminates available upon request:
 - Holographic images
 - Special OVD images
 - UV images

Communications Interface

- » USB 1.1 (Standard)
- » Factory Installed Options
 - Built-In Ethernet
 - Bi-directional Parallel with ECP support

Mechanical

- » Width: 27.5" (699mm) not including exit hopper
- » Depth: 9.7" (246mm)
- » Height: 11.5" (292mm)
- » Weight: 35 lbs (15.9kg)

Electrical

- » 110 - 240 Volts AC, 50/60 Hz
- » FCC Class A, UL, CUL, & CE approved

Environmental

- » Operating temperature: 50°F to 95°F (10°C to 35°C)
- » Operation humidity: 20% to 80% non-condensing
- » Storage temperature: -4°F to 158°F (-20°C to 70°C)
- » Storage humidity: 5% to 90% non-condensing
- » Ventilation: Free air

Options

- » ID/Key security printing feature
- » Magnetic Encoder
- » Smart Card Contact Station
- » Smart Card Contactless encoder/reader
- » Smart Card Contact encoder/reader
- » Warranty programs

Optimized for use with Zebra media.



Zebra Technologies Corporation



An ISO 9001 registered company ©2004 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. P640i - 11/04

North America

Zebra Technologies Corporation Card Printer Solutions

1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra Technologies Corporation Card Printer Solutions

The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation Card Printer Solutions

16 New Industrial Road
#05-03 Hudson TechnoCentre
Singapore 536204
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America

Zebra Technologies Corporation Card Printer Solutions

9800 NW 41st Street, Suite 220
Doral, FL 33178
USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com